



The spray system produces clear and transparent ice cubes and the patented **Bright Cube** shape grants a longer lasting cube for you to enjoy your cold drinks

Self contained ice maker.

Up to 70kg production per 24/hr of medium ice cube.  
42kg storage bin.

Complete with legs, water & drain hoses + 1 ice scoop.  
10 AMP power supply.

291 mm drain height including legs to finished floor.



## ICE PRODUCTION



### Air Cooled Unit

Air Temp.		Water Temperature			
		32°	21°	15°	10°
°C		21°	15°	10°	
°F		70°	60°	50°	
10°		<b>64</b>	<b>68</b>	<b>70</b>	<b>72</b>
50°		141	150	154	159
21°		<b>57</b>	<b>61</b>	<b>63</b>	<b>65</b>
70°		126	134	139	143
32°		<b>51</b>	<b>55</b>	<b>57</b>	<b>59</b>
90°		112	121	126	130
38°		<b>40</b>	<b>43</b>	<b>45</b>	<b>47</b>
100°		88	95	99	104

### Water Cooled Unit

Air Temp.		Water Temperature			
		32°	21°	15°	10°
°C		21°	15°	10°	
°F		70°	60°	50°	
10°		<b>62</b>	<b>67</b>	<b>68</b>	<b>70</b>
50°		137	148	150	154
21°		<b>57</b>	<b>62</b>	<b>64</b>	<b>66</b>
70°		126	137	141	146
32°		<b>51</b>	<b>56</b>	<b>58</b>	<b>60</b>
90°		117	128	132	137
38°		<b>49</b>	<b>53</b>	<b>56</b>	<b>57</b>
100°		108	117	123	126

## CUBE TYPE



**20g weight**  
**BRIGHT CUBE**  
32mm x 35mm x 37mm

The Bright Ice Cube, appreciated for its versatility, is perfect for use in ice buckets, whiskey on the rocks, cocktails and appetisers. The crystal clear appearance of the Bright Cube makes it essential when a high quality is required.

## CONTROL PANEL



Switch On/Off

Ice size regulation screw

## BIN CAPACITY

42 kg - 93 lbs | 2100 pcs

## DIMENSIONS

W x D x H (mm)

700 x 580 x 910/1030

760 x 630 x 1070

## OPERATING REQUIREMENTS

Rejected Heat 1968 W

Air Volume 310 m<sup>3</sup>/h
















220-240/50/1



R134a GWP = 1430

MIN		MAX	
10°C (50°F)		40°C (104°F)	
5°C (41°F)		35°C (95°F)	
- 10 %		+ 10 %	
1 Bar (14 psi)		5 Bar (70 psi)	

## SPECIFICATIONS

	 cond	 comp. W	 ABS. W	 Fuse	 kWh/100kg	 L / hr	 kg	 lbs	 kg	 lbs	 Ton CO2 equiv.
<b>CS70 A</b>		1317	880	10	26.3	5.98	57	126	69	152	0.56
<b>CS70 W</b>		1317	560	10	21.1	37.8	57	126	69	152	0.53

